

Assigned: Tuesday 1 September

Due: Monday 7 September 11:59 pm

Objectives:

- Reinforce Scheme basics
- Recall how to write recursive procedures over lists and numbers using named `let` and tail recursion
- Explore clever uses of higher-order procedures

Collaboration: This homework assignment must be completed individually.

A common problem in the AI subfield of machine learning is to do regression on a set of points. That is, assume points are observations from some unknown function, and we wish to infer the function so that we may make predictions by interpolating between these points.¹ One approach to this problem is to model the unknown function as a polynomial, which means one must determine the coefficients. In this assignment, we'll develop some useful Scheme functions for defining and evaluating “encapsulated” polynomials.

1. Add the procedures `left-section`, `right-section`, and `dot-product` from your in-class lab. Be sure to cite the originals appropriately and attribute the contributions of your partner(s).
2. Using named `let`² and tail recursion,³ write the procedure `(iota num)` that produces the list of numbers from 0 to `num - 1` in order. For example,

```
> (iota 5)
(0 1 2 3 4)
```

Your solution must *not* call `reverse`; if your original attempt produces results in the wrong order, you must think about building the result in the opposite order.

3. Write a procedure, `(polynomial-term c n)` that returns the function $f(x) = c \cdot x^n$.

```
> (define two-x-cubed (polynomial-term 2 3))
> (two-x-cubed 1) ; 2 * 1 * 1 * 1
2
> (two-x-cubed 3) ; 2 * 3 * 3 * 3
54
> (define three-x-squared (polynomial-term 3 2))
> (three-x-squared 1) ; 3 * 1 * 1
3
> (three-x-squared 5) ; 3 * 5 * 5
75
> ((polynomial-term 5 4) 2) ; 5 * 2^4
80
```

4. Write a procedure `(polynomial coeffs)` that takes a list of coefficients for the terms x^0 , x^1 , x^2 , ... of a polynomial and produces a function that takes a single value, evaluating the polynomial given those coefficients at that value.

¹For example, see AIMA section 18.2, pp. 695–697, or <https://en.wikipedia.org/wiki/Kriging>.

²If you've forgotten how to write a named `let`, see, e.g., Dyvbig, *Recursion and Iteration* <http://www.scheme.com/tspl4/control.html#./control:s20>

³If you've forgotten about tail recursion, see e.g., Davis et al. *Helper Recursion*, <http://www.cs.grinnell.edu/~weinman/courses/CSC261/2015F/misc/recursion-patterns.html>

```

; Create the polynomial  $f(x) = 1*x^0 + 4*x^1 = 1 + 4*x$ 
> (define line (polynomial (list 1 4)))
> (line 5) ; Evaluate  $f(5) = 1 + 4*5$ 
21
; Create the polynomial  $g(x) = 1 + 4*x + 3*x^2 - 2*x^3$ 
> (define cubic (polynomial (list 1 4 3 -2)))
> (cubic 5) ; Evaluate  $g(5) = 1 + 4*5 + 3*5^2 - 2*5^3$ 
-154

```

Note: Make your solution as concise as possible and do *not* (explicitly) use recursion.

5. Recall that the derivative of a polynomial-term may be given by $\frac{d}{dx}c \cdot x^n = c \cdot n \cdot x^{n-1}$. Write a procedure (polynomial-derivative-coeffs *coeffs*) that takes a list of coefficients and produces a list of coefficients of polynomial's derivative.

```

> (polynomial-derivative-coeffs (list 1 4 3 -2))
(4 6 -6)

```

6. It can often be tedious to manually compose the same function with itself several times. Often, we do not know in advance how many times a procedure should be applied.

Write a new procedure, *nest*, as follows. *nest* takes two parameters, a unary procedure *f* and an integer *n*. The value produced is a new procedure that results from composing together *n* copies of *f*.

Note that *n* must be at least 1 for *nest* to make sense.

```

> (define 1-s left-section)
> (define plus5 (nest (1-s + 1) 5))
> (plus5 6)
11
> (define duplicate (lambda (val n) ((nest (1-s cons val) n) null)))
> (duplicate "hello" 5)
("hello" "hello" "hello" "hello" "hello")
> (define second-derivative (nest polynomial-derivative-coeffs 2))
> (second-derivative (list 1 4 3 -2))
(6 -12)

```

7. Write a procedure (polynomial-deriv *coeffs n*) that takes a list of polynomial coefficients *coeffs* and a strictly positive integer *n* and produces a procedure that takes a single value and evaluates the *n*th derivative of the polynomial with the given coefficients at that value.

```

> (define d2/dx2-cubic (polynomial-deriv (list 1 4 3 -2) 2))
> (d2/dx2-cubic 5)
-54

```

8. Write a procedure (non-zero-coefficients *coeffs*) that takes a list of coefficients for the terms x^0, x^1, x^2, \dots of a polynomial with terms $c_n \cdot x^n$ and produces the values of *n* (in ascending order) for which $c_n \neq 0$.

```

> (non-zero-coefficients (list 1 4 0 -2))
(0 1 3)
> (non-zero-coefficients (polynomial-derivative-coeffs (list 1 4 0 -2)))
(0 2)

```

What to turn in

Your submission should include the following

- `polyomial.scm`, your completed implementation of all procedures above
- `test-polynomial.scm`, a separate driver program that demonstrates your procedures are correct (use examples other than those provided); use `(load "polynomial.scm")` to access the other file's procedures
- A single PDF containing (merged)
 - Your Scheme files
 - A transcript of your driver program's output

A missing PDF or files in any other format will receive a zero.

Acknowledgements

Problems 3 and 4 are adapted from S. Rebelsky and J. Weinman, *Exam 3: Sophisticated Scheming*, CSC151 2010S.
Problem 6 is adapted from J. Davis and J. Weinman, *Exam 3: Sophisticated Scheming*, CSC151 2011S.

